

# RAPID ELAST



A rubber-like material for accelerated designing and prototyping of elastomeric products

## DESIGN AND TEST ELASTOMERIC PARTS

Figure 4 ELAST-BLK 10 is a material suited for the prototyping and design of a wide variety of elastomeric parts. Producing parts in a fraction of the time required to produce molded parts, this material accelerates the design and iteration of new concepts with rubber-like functional prototypes for industrial and consumer goods applications.

### Liquid Material

MEASUREMENT	CONDITION	VALUE	
Viscosity	@ 25 °C (71 °F)	1200 cps	
Color		Black	
Solid Density	@ 25 °C (77 °F)	1.13 g/cm <sup>3</sup>	0.041 lb/in <sup>3</sup>
Liquid Density	@ 25 °C (77 °F)	1.06 g/cm <sup>3</sup>	0.038 lb/in <sup>3</sup>
Package Volume		1 kg bottle - Figure 4 Standalone 10 kg container - Figure 4 Production	
Layer Thickness (Standard Mode)		0.10 mm	0.004 in
Vertical Build Speed (Standard Mode)		47 mm/hr	1.9 in/hr

## APPLICATIONS

- Design verification and validation and testing of:
  - Hoses
  - Tubes
  - Weatherstripping
  - Seals
  - Grommets
  - Gaskets
  - Spacers and other vibration dampening components

## BENEFITS

- Verify, modify and optimize designs of elastomeric parts prior to production
- Excellent shape recovery
- Realistic rubber look and feel

## FEATURES

- Medium softness/stiffness
- High elongation at break
- Excellent compressive characteristics

